

APPLICATION FOR UNITED STATES LETTERS PATENT

TITLE:

~~QUONSET TYPE~~SEMI-CYLINDRICAL TYPE PARACHUTE

INVENTOR:

Roy L. Fox, Jr., Rt 1, Box 32A, Belleville, WV, (US) 26133

~~QUONSET TYPE~~SEMI-CYLINDRICAL TYPE PARACHUTE

1. Field of the Invention:

[001]___ The present invention relates to the field of parachutes and, more particularly, to a novel type of parachute that will equal, or surpass, the performance characteristics of a conventional ~~circular/hemispherical~~semi-spherical ballistic type parachute and, in some ways, controllably mimic the performance characteristics of a higher performance, parafoil type, gliding wing, parachute.

2. Description of the Prior Art

[002]___ In general terms, for personnel use, and for the aerial delivery of cargo, there are two types of parachutes in use today. One type is the ~~circular/hemispherical~~semi-spherical ballistic, drag producing, ~~ballistic~~ parachute, commonly known in the trade as a round parachute, although it is typically constructed as a polygon. The other type is a ram-air inflatable wing, which is a lift producing, gliding parachute, commonly known in the trade as a parafoil or a square parachute, although it is generally rectangular or elliptical in plan form.

a. Ballistic Parachutes

[003]___ The ~~circular/hemispherical~~semi-spherical ballistic, type parachute has been in use for many, many, decades and continues to be the most widely used parachute type, by a huge margin. Performance of this type of parachute is almost entirely dependent on drag because it has extremely little gliding or lift generating capability. In many instances, having no true gliding capability, drifting only where the wind carries it, is not only acceptable, it is quite desirable. For instance; during mass parachute deployments of military troops or equipment, the non-gliding feature of the ~~circular/hemispherical~~semi-spherical ballistic, type parachutes allows

these uncontrolled parachutes to generally maintain relative separation. This feature greatly reduces the opportunities for parachute collisions and subsequent entanglements.

[004] Semi-spherical ballistic parachute canopies are occasionally provided with directional venting, which allows them to be steered to a desired heading, but their gliding performance is extremely low. Even though this steering technique has been known for many years, parachutes having this configuration are used very little and, when used, are used almost exclusively as personnel parachutes. By lacking the capability for traversing through an air mass and the high cost for guidance and control, this type of parachute has not generally been considered to be sufficiently effective for guided cargo aerial delivery systems.

[005] While it is much less costly to fabricate a semi-spherical ballistic type parachute than a parafoil type parachute, of the same general size, construction of the semi-spherical ballistic type of parachute is, nevertheless, not especially efficient use of the fabric from which it is constructed. A typical semi-spherical ballistic type parachute canopy is generally constructed from multiple triangular gore panels that radiate from a central point. Generally, the gore panels are truncated to provide the parachute canopy with a centrally located vent and, occasionally, the triangular gore shape is slightly modified to provide a more aerodynamically appropriate shape for a specific application. Extending outward from the canopy skirt, generally from the radial seams that join the gores, are suspension members with a length that generally approximate the constructed diameter of the canopy.

[006] The horizontal profile of the canopy of a ballistic parachute, when inflated into a spherical cap, will be less than the surface area of the canopy resulting in a projected diameter that is reduced by approximately one third of its constructed diameter. An undesirable

consequence of a semi-spherical ballistic canopy that has been effectively reduced by approximately 33.3% of its constructed diameter is that it projects a drag area that has been reduced by approximately 44.4% of its constructed area.

b. Parafoil-type Parachutes

[007] ~~The parafoil type parachute is a ram-air inflatable wing and is, therefore, very dependent on~~ requires a relatively fast forward glide velocity to produce lift; just as the forward velocity of an airplane wing produces lift. The parafoil type parachute is also quite ~~steerable, making it highly~~ maneuverable. The gliding and lift producing characteristics of the parafoil type parachute, coupled with omnidirectional steering, allows it to glide long distances and be accurately maneuvered to a precise landing point. The attributes of the parafoil type parachute make it the overwhelming choice for modern day skydivers and military operations when precision landing of troops or cargo is desirable.~~the goal.~~

[008] The very features that make the parafoil type parachute extremely desirable for some select applications make it much less desirable for other applications, however. Properties that allow the parafoil type parachute to glide long distances, and be highly maneuverable, require that it have a costly guidance and control system for delivering cargo to precise target locations or that it be operated by only highly skilled parachutists when used as a personnel parachute.

~~The very features that make the parafoil type parachute extremely desirable for some select applications make it much less desirable for other applications, however. Properties that allow the parafoil type parachute to glide long distances, and be highly maneuverable, require that it have a costly guidance and control system for delivering cargo to precise target locations or that it be operated by only highly skilled parachutists when used as a personnel parachute.~~

[009] The ~~circular/hemispherical~~semi-spherical ballistic, type parachute, even coupled with a guidance and control system, is typically inadequate for accurate target attainment but the parafoil type parachute may have excessive capabilities and, in some instances, introduce more problems than it solves. The properties that permit this type of parachute to be guided to a very specific target will also allow it to reach a point very distant from the desired target if not steered correctly. Additionally, even though parachutists using the parafoil type parachutes are typically very skilled, some number of deaths occur each year as the result of high speed landings or midair collisions with fellow parachutists and/or the ~~ensueing~~ensuing entanglements that cause crash landings after the entangled parafoils lose their forward velocity and, consequently, their lift. Moreover, the parafoil type parachutes are very labor intensive to fabricate and are, therefore, quite costly when compared to a ~~circular/hemispherical~~semi-spherical ballistic type parachute of the same general size.

~~Circular/hemispherical parachute canopies are occasionally provided with directional venting, which allows them to be steered to a desired heading, but their gliding performance is extremely low. Even though this steering technique has been known for many years, parachutes having this configuration are used very little and, when used, are used almost exclusively as personnel parachutes. Because of very little capability for traversing through an air mass, and the high cost for guidance and control, this type of parachute has not generally been considered to be sufficiently effective for guided cargo aerial delivery systems.~~

[010] Many large scale users of parachute systems, such as military organizations, find themselves in a dilemma: Generally, a choice must be made between a simple low cost, ballistic, ~~circular/hemispherical~~semi-spherical ballistic type parachute system, having very little target acquisition capability, or a high cost, high performance, parafoil type parachute system, requiring

a sophisticated guidance and control system or highly skilled parachutists to operate reliably. In actual practice, many large scale users of parachutes must maintain both types of parachute systems in their inventory.

~~BACKGROUND OF THE INVENTION~~

~~There are two types of parachute systems in general use today, for large scale users, such as military organizations. One type features the circular/hemispherical, generally ballistic, parachutes, having very little capability for traversing an air mass, and the other features the high performance, inflatable wing, parafoils that require highly sophisticated guidance and control devices, or highly skilled parachutists, to operate reliably.~~

~~Generally speaking, both the ballistic and high glide types of parachute systems must be kept in inventory, and operations managers must chose between one or the other, because the systems are not interchangeable and there is no system to bridge the gap between the two.~~

~~While it is much less costly to fabricate a circular/hemispherical type parachute than a parafoil type parachute, of the same general size, construction of the circular/hemispherical type of parachute is, nevertheless, not especially efficient when the amount of fabric used in the construction is considered. A typical circular/hemispherical type parachute canopy is generally constructed from multiple triangular gore panels that radiate from a central point, and is depicted by Fig 6. Generally, the gore panels are truncated to provide the parachute canopy with a centrally located vent and, occasionally, the triangular gore shape is slightly modified to provide a more aerodynamically appropriate shape for a specific application. Extending outward from the canopy skirt, generally from the radial seams that join the gores, are suspension members with a length that generally approximate the constructed diameter of the canopy.~~

[011] When properly inflated, the ~~circular/hemispherical~~semi-spherical ballistic type parachute canopy will be reduced around its entire circumference, resulting in a projected diameter that is reduced by approximately one third of its constructed diameter. An undesirable consequence of a ~~circular/hemispherical~~semi-spherical ballistic canopy that has been effectively reduced by approximately 33.3% of its constructed diameter is that it projects a drag area that has been reduced by approximately 44.4% of its constructed area. The outermost circle of Fig 4 illustrates the constructed area of a ~~circular/hemispherical~~semi-spherical ballistic type parachute canopy and the shaded portion of the figure depicts the relative inflated size. Additionally, the ~~circular/hemispherical~~semi-spherical ballistic parachute has very little capability for altering its ballistic path to enable it to reach a specific target.

[012] Parafoil type parachute canopies are multiple cell, airfoil shaped, ram-air inflatable, wings made of many complex panel shapes requiring demanding fabrication processes. To establish the rigging angle necessary to achieve a desired glide angle, and maintain the desired airfoil shape, great variation in the length of the suspension lines is necessary, depending on their designated locations. When properly inflated, a parafoil type parachute has a generally rectangular, or elliptical, plan form, and, quite frequently, has a span that is approximately 250% of its chord. While parafoils have very impressive flight characteristics, if not properly controlled during flight, they can miss their intended targets by huge amounts and, if not properly controlled at landing, can severely damage delivered payloads and injure or kill parachutists.

~~It is therefore an object of the invention to provide a novel parachute design that will efficiently fulfill all the performance requirements of the low cost, low performance, circular/hemispherical~~

~~type parachute and many of the requirements of the high cost, high performance, parafoil type parachute with a simple to construct, low cost, parachute.~~

~~It is another object of the invention to provide a parachute having a canopy with a generally rectangular plan form.~~

~~It is another object of the invention to provide a parachute having inverted gores.~~

~~It is another object of the invention to provide a parachute having canopy segments.~~

~~It is another object of the invention to provide a parachute having longitudinal seams.~~

~~It is another object of the invention to provide a parachute having, downwardly converging, suspension lines.~~

~~It is another object of the invention to provide a parachute having riser assemblies.~~

~~It is another object of the invention to provide a parachute having canopy end panels.~~

~~It is another object of the invention to provide a parachute that is selectively ballistic or gliding.~~

~~It is another object of the invention to provide a parachute that is selectively steerable.~~

~~It is another object of the invention to provide a parachute with a selectively variable descent rate.~~

~~It is another object of the invention to provide a parachute with efficient materials utilization.~~

SUMMARY OF THE INVENTION

[013] In accordance with the present invention, there is provided a very simple technique that can be used to design a parachute canopy that will provide approximately 50% more projected drag area than a ~~circular/hemispherical~~semi-spherical ballistic type parachute canopy when constructed from a given amount of fabric. Furthermore, this basic canopy design will produce a parachute that will have, selectively, moderate glide performance along with favorable maneuvering capabilities. This novel parachute, while descending, can transition, controllably, from ballistic, to gliding, and from gliding to ballistic, as circumstances dictate. Beyond that, this parachute design allows for a simple control feature that enables its vertical velocity to be adjusted so that it exceeds the nominal descent rate or decreased to less than the nominal descent rate. The inflated canopy shape of this parachute is roughly that of a half cylinder and it is referred to as a ~~quonset-type~~semi-cylindrical type parachute.

[014] The canopy for the ~~quonset-type~~semi-cylindrical type parachute is fabricated of gores, somewhat like the gores of a ~~circular/hemispherical~~semi-spherical ballistic parachute canopy, but they are inverted, relative to a ~~circular/hemispherical~~semi-spherical ballistic parachute, and appear as narrow canopy segments, joined side by side, with longitudinal seams, ~~as illustrated by Fig 1.~~ This geometry results in a parachute canopy that is constructed as a generally rectangular plan form, instead of a circular plan form. ~~One gore is illustrated by Fig 2. Two gores, inverted, illustrated by Fig 3, compose a canopy segment. Fig 3 further illustrates that a canopy segment can be cut from a single piece of fabric, as an alternative technique.~~ The simple design feature of inverting the gores has a profound impact on the resulting canopy shape and, consequently, the parachute performance capabilities.

[015] A ~~quonset-type~~semi-cylindrical type parachute canopy, constructed from an identical amount of fabric as a ~~circular/hemispherical~~semi-spherical ballistic canopy, when properly

inflated, will have a size reduction in the chordwise direction only and will, therefore, have a projected drag area that is approximately 66.7% of the constructed area. The outermost lines of Fig 5 illustrate the constructed area of a ~~quonset type~~ semi-cylindrical type parachute canopy and the shaded area of the figure illustrates the relative inflated size. As the result of this configuration, the projected drag area of the ~~quonset type~~ semi-cylindrical type parachute canopy, for an equal amount of fabric, has approximately 150% of the projected drag area of a ~~circular/hemispherical~~ semi-spherical ballistic type parachute canopy. For the user, this means that, for a specific amount of suspended weight, the canopy size can be reduced by approximately 33.3%. Or, for a specific amount of fabric, the amount of suspended weight can be increased by approximately 50%.

[016] When compared to a ~~circular/hemispherical~~ semi-spherical ballistic parachute, a parafoil type parachute, of the same general size, is very costly. In many instances, the increased cost for the parafoil type parachute is considered to be worthwhile because it provides a parachute that can efficiently traverse an air column in which it is descending and has good target reaching capabilities. However, if the parafoil type parachute is not properly controlled, its high performance features can cause it to miss the intended target by huge factors. Additionally, because of the high velocity gliding feature of the parafoil type parachute, landings are a particular problem. To reduce the velocity of autonomously guided parafoil type cargo delivery systems, it is very desirable to have an accurate altitude sensing device, such as a radar altimeter, coupled to the controlling device to cause a precisely timed flared landing maneuver. Obviously, such sophisticated equipment is very costly. For parachutists, on the other hand, it is necessary to clearly see the landing spot and have the proper skills to correctly perform the precisely timed flared landing maneuver, at the precise altitude, that will contribute to landing safely.

[017] The ~~quonset type~~ semi-cylindrical type parachute has improved ballistic performance over the ~~circular/hemispherical~~ semi-spherical ballistic type parachute and, selectively, many of the steering and maneuvering characteristics of the parafoil type parachute, although to a lesser degree. Moreover, by landing ballistically, the ~~quonset type~~ semi-cylindrical type parachute is not dependent on a precisely timed flared landing maneuver to decrease landing velocity.

[018] In some instances, it is quite desirable to maneuver a parachute to a point above a target and then maintain that general position. The unique performance capabilities of the ~~quonset type~~ semi-cylindrical type parachute allows this to be done quite conveniently.

[019] The ~~quonset type~~ semi-cylindrical type parachute can be deployed as a ballistic parachute then, if desired, it can selectively transition to become a gliding, steerable, parachute, having performance characteristics somewhat like the parafoil type parachute, to reach a specific target area. Over the target, or on the glide path to the target, the parachute can, selectively, transition into a ballistic parachute, again. Depending on specific needs, the descent rate of the ~~quonset type~~ semi-cylindrical type parachute can be altered to cause a rate that is above nominal or below nominal. This combination of features is not attainable with either the ~~circular/hemispherical~~ semi-spherical ballistic type parachute or the parafoil type parachute.

[020] Even though the ~~circular/hemispherical~~ semi-spherical ballistic type parachute is considered to be generally ballistic, by retracting the suspension members on one side and/or extending the suspension members on the opposite side, the canopy skirt will be caused to tilt, relative to horizontal, and relatively high pressure air from the canopy interior will vent from beneath the elevated side of the canopy skirt and push the parachute in the opposite direction.

Because the inflated parachute canopy is roughly hemispherical, not at all wing-like, extremely little lift is generated and the traversing movement, known as slipping, is very inefficient.

[021] It is not uncommon for slipping maneuvers to be accomplished with slip-riser assemblies. Conventionally, one slip-riser assembly is used for the left side of the parachute assembly and another slip-riser assembly is used for the right side. Each slip-riser assembly typically consists of a front riser leg joined to a rear riser leg and is configured to cause a rear riser leg extension as the result of a front riser leg retraction, and vice versa. This process, while enabling a ~~circular/hemispherical~~ semi-spherical ballistic parachute canopy to move transversally, will not cause it to quickly change heading by spinning or spiraling as part of the process, however. The insignificant rotational capability provides a parachutist, or the operator of a ~~circular/hemispherical~~ semi-spherical ballistic parachute cargo delivery system, very little heading control, relative to wind direction. A choice of heading may be especially desirable when landing. Statistically, and randomly, 25% of all landings, when using conventional ~~circular/hemispherical~~ semi-spherical ballistic parachutes, will be landings with forward drift, landings with left or right drift will be split evenly, with 25% in each direction, and 25% will be landings while drifting to the rear. Regardless of the skill of the parachutist, a rearward landing is more likely to result in injury than is a landing with drift in any other direction. Use of the ~~quonset type~~ semi-cylindrical type parachute will allow a great majority of landings to have the most desirable heading for the particular circumstance.

~~It is quite feasible for the quonset type parachute to utilize conventional slip-riser assemblies if controlled maneuvering is desired. When using the slip-riser maneuvering technique, the risers for both sides of the parachute can be manipulated, in unison, to cause a forward glide. By reversing the riser positions, a rearward glide will be produced. Because the quonset type~~

~~parachute canopy plan form is much more wing-like than the canopy of the circular/hemispherical type parachute, the gliding performance is considerably more pronounced, and efficient, than that of a parachute having a circular/hemispherical canopy. If the riser assembly on only one side of the parachute is manipulated, the quonset type parachute will make a heading change and the canopy can then be caused to glide in a new direction. Or, if desired, it can simply maintain the new heading, without glide. If an increased rate of descent is desired, the riser assembly on one side can be manipulated to cause a turn and, if the riser position remains unchanged, a spiraling turn will result.~~

~~Spiraling turns are aerodynamically inefficient and the rate of descent will increase as a result. If, on the other hand, the riser assembly on one side is manipulated to cause a turn in one direction and the opposite riser assembly is manipulated in a similar fashion, the quonset type parachute canopy will twist to become somewhat propeller-like, and spin about its vertical axis, producing lift, just as the spinning blades of a helicopter produce lift if the helicopter engine has lost power. Logically, when the parachute canopy begins producing lift it will have a decrease in its relative rate of descent.~~

~~The very unique maneuvering capabilities of the quonset type parachute, coupled with excellent economy of construction, is not known to exist with any other parachute type.~~

~~As for parachutes of many other types, the designer of a quonset type parachute canopy can select from fabric offering the most desirable degree of permeability for a specific application, or the canopy can be made from strips of fabric, or ribbons, or be produced with specifically sized and located orifices, to produce a canopy with a specific geometric porosity and/or directional venting.~~

~~It has been learned that the performance of the quonset type parachute can be enhanced by having a panel installed in each end of the semi cylindrical canopy to inhibit transverse airflow from the canopy interior. A semicircular end panel, completely filling the opening at each end of the quonset parachute canopy, as depicted by Fig 1, is most effective but a partial panel, such as one shaped as a crescent, is somewhat effective and has less bulk than a semicircular end panel. However, a complete semi circular end panel will cause the inflated canopy shape to become somewhat elliptical, and will slightly increase the canopy span. If installed, end panels are considered to be components of the parachute canopy assembly.~~

~~As is true for any type of wing like gliding device, the gliding performance of the quonset type parachute can be enhanced by increasing the span ratio, relative to the chord. The size and aspect ratio of the quonset type parachute canopy is primarily dependent on the number of canopy segments utilized and/or the size of the canopy segments.~~

~~Depending on loading conditions, it may be desirable to install suspension lines on the end panels of the quonset type parachute canopy. Specific loading factors will dictate any end panel reinforcement required as well as the number of suspension lines required and the precise shape of the end panel will dictate the length of the suspension members.~~

~~To properly manage the opening forces that a parachute is subjected to, it is frequently desirable to prolong the opening process of the parachute canopy by a technique known as reefing. It has been learned that the quonset type parachute is compatible with all conventional reefing techniques such as peripheral reefing, spanwise reefing, or slider reefing. Because of its simplicity and low cost, it is expected that slider reefing will typically be chosen when reefing is desired for the quonset type parachute.~~

~~Because of the very simple shape, the quonset type parachute can easily be constructed in modular form. For large scale quonset type parachutes, modularity will allow convenient disassembly for handling or repair.~~

~~As with all parachutes of all types, the parachute size, the suspended weight, and the predicted aerodynamic forces will dictate the number, and strength, of all materials for the design and construction of a quonset type parachute, in addition to dictating the strength of seams and joints that must be used.~~

[022] It is therefore an object of the invention to provide a novel parachute design that will efficiently fulfill all the performance requirements of the low cost, low performance, semi-spherical ballistic type parachute and many of the requirements of the high cost, high performance, parafoil type parachute with a simple to construct, low cost, parachute.

[023] It is another object of the invention to provide a parachute having a canopy with a generally rectangular plan form.

[024] It is another object of the invention to provide a parachute that is selectively ballistic or gliding.

[025] It is another object of the invention to provide a parachute that is selectively steerable.

[026] It is another object of the invention to provide a parachute with a selectively variable descent rate.

[027] It is another object of the invention to provide a parachute with efficient materials utilization.

BRIEF DESCRIPTION OF THE DRAWINGS

[028] A complete understanding of the present invention may be obtained by reference to the accompanying drawings, when considered in conjunction with the subsequent, detailed description, in which:

[029] Figure 1 is a perspective view of a properly inflated ~~quonset type~~ semi-cylindrical type parachute having a canopy assembly, ~~inverted gore~~ trapezoidal gores, canopy segments, longitudinal seams, end panels, suspension lines, and slip-riser assemblies;

[030] Figure 2 is a plan top view of an ~~inverted gore~~ trapezoidal gore;

[031] Figure 3 is a plan top view of a canopy segment comprised of two ~~inverted gore~~ trapezoidal gores;

[032] Figure 4 is a plan top view of a conventional ~~circular/hemispherical~~ semi-spherical ballistic parachute canopy, having a constructed area and an inflated area;

[033] Figure 5 is a plan top view of a ~~quonset type~~ semi-cylindrical type parachute canopy, having a constructed area and an inflated area;

[034] Figure 6 is a plan top view of a parachute canopy having conventional ~~circular/hemispherical~~ semi-spherical ballistic geometry; and

[035] Figure 7 is an elevation ~~front~~ view of a semicircular end panel.

[036] For purposes of clarity and brevity, like elements and components will bear the same designations and numbering throughout the FIGURES.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[037] Figure 6 illustrates a conventional, semispherical ballistic parachute 24 in plan view. The semispherical ballistic parachute 24 is constructed of a plurality of gores arranged radially around a central circular panel or vent. The gores are generally trapezoidal in shape, with a smaller base disposed at the center of the semispherical ballistic parachute 24 and a larger base at the perimeter or “skirt” of the parachute. Each of the long sides 28 of each gore 26 are conjoined with the opposing long side of the adjacent gores, forming a radial seam 30 between the gores 26. The long sides 28 of each gore 26 may be straight, or arcuate, to provide a shape more of a spherical segment when the parachute is inflated.

[038] In Figure 4, the horizontal or plan areas of the uninflated and inflated semispherical ballistic parachute 24 are compared. The uninflated area represents the area of the deflated parachute on a flat horizontal surface, and is proportional to the amount of fabric required to construct the parachute. The inflated area 34, shown within the cross-hatched area of Figure 4, represents the area of the inflated semispherical ballistic parachute 24, when it has taken the shape of a spherical segment, projected on a horizontal plane. This horizontal inflated area 34 is proportional to the amount of drag provided by the ballistic semispherical parachute. The ratio of the projected uninflated area 32 to the inflated area 34 on the horizontal plane represents the drag efficiency provided by the parachute design.

[039] To achieve the objectives of providing a parachute design with an improved drag efficiency over a ballistic parachute, in addition to providing one with some gliding or maneuvering improvements over a ballistic parachute, a semi-cylindrical parachute 10 is provided, as shown in Figure 1. The semi-cylindrical parachute 10 is comprised of a canopy

assembly 12, which in turn is comprised of a number of canopy segments 16. The preferred number of canopy segments 16 comprising the canopy assembly 12 is seven. At either end of the canopy assembly 12 is an end panel 18. Each end panel 18 has a curved, preferably semi-circular upper edge, which forms a seam with the outer longitudinal edge of the adjacent canopy panel. The completed canopy has, when inflated, a generally semi-cylindrical shape around the horizontal axis.

[040] A number of suspension lines 20 are connected to the canopy assembly 12, from which the supported load is suspended. The upper end of each suspension line 20 is attached to the skirt of the canopy assembly 12 at a seam between adjacent canopy segment 16 and between end panels 18 and adjacent canopy segment 16. The lower ends of the suspension lines 20 are assembled together with a pair of slip-riser assemblies, as commonly used in the art.

[041] In Figure 2, one of the two gores 14 which comprises each canopy segment 16 is illustrated. Each gore 14 is generally in a trapezoidal shape fabricated from a single layer of fabric, with two parallel bases; a longer base 38 and a shorter other base. Two longitudinal sides 42 of the gore taper inward from the larger base to the shorter base 40. The longitudinal sides 42 may be straight or arcuate, depending on the desired shape of the inflated canopy.

[042] In Figure 2, an assembled canopy segment 16 is illustrated. Each canopy segment 16 is comprised of two gores 14, in reverse orientation to each other with the two longer bases 38 abutting to form a centerline span 44. The two shorter bases 40 of the gores 14 are parallel and at opposite ends of the canopy panel.

[043] The end panel 18 is illustrated in Figure 8. It is comprised of a single layer of fabric and is cut into a shape with a substantially straight lower edge 46 and an arcuate or curved upper

edge 36. The ends of the upper edge 36 are disposed at either end of the lower edge 46. In the preferred embodiment, the upper edge 36 is semicircular in shape, with a center of radius located at the center of the lower edge 46.

[044] The parts of the canopy are illustrated in Figure 8, prior to assembly. A plurality of canopy segments 16, preferably seven, are aligned laterally with centerline spans 44 and either ends of the canopy segments collinearly aligned. The longitudinal sides 42 of adjacent canopy segment 16 are conjoined in a seam. The upper edge 36 of each end panel 18 and the outer longitudinal side 42 of the outer canopy segment 16 are conjoined in a seam; forming a single layer canopy.

[045] Figure 1 is a perspective view of a ~~quonset type~~ semi-cylindrical type parachute assembly 10. This ~~quonset type~~ semi-cylindrical type parachute assembly 10 consists of a generally semi-cylindrical canopy assembly 12, of an approximately 2.0:1 span to chord aspect ratio when properly inflated, comprised of a plurality of canopy segments. Each canopy segment is comprised of a single layer of fabric having two longitudinal edges and two parallel end edges. This semi-spherical type parachute assembly has ~~inverted-gore~~ trapezoidal gores 14, combined as canopy segments 16, having anhedral arc incorporated as the result of the ~~inverted-gore~~ trapezoidal gore 14 orientation, along with semicircular end panels 18, in addition to suspension lines 20, and slip-riser assemblies 22, that when combined, in series, have a length that is approximately equal to 100% of the canopy assembly 12 span.

Figure 2 is an ~~inverted-gore~~ 14

Figure 3 is a ~~canopy segment~~ 16

~~Figure 4 is a top view of a conventional circular/hemispherical parachute canopy having a constructed area and an inflated area~~

~~Figure 5 is a top view of a quonset parachute canopy having a constructed area and an inflated area~~

~~Figure 6 is a circular/hemispherical parachute canopy with conventional canopy geometry~~

~~Figure 7 is a semi-circular end panel 18~~

[046] To fabricate the semi-cylindrical parachute 10, ~~B~~beginning with a selected inflated area, of an approximately 2.0:1 span to chord aspect ratio; multiply the span dimension by 0.392 to obtain a centerline chord dimension for the design of an ~~inverted-goretrapezoidal gore 14~~.

Divide the span dimension by the desired number of canopy segments 16, which is seven ~~for this illustration in the preferred embodiment~~, to obtain a design dimension for the ~~the span, or longer base 38~~ of each ~~inverted-goretrapezoidal gore 14~~. Multiply the span dimension of the ~~inverted-goretrapezoidal gore 14~~ by 0.8 to obtain a design dimension for the skirt, ~~or a shorter base 40~~ of each ~~inverted-goretrapezoidal gore 14~~. Multiply the resulting ~~inverted-goretrapezoidal gore 14~~ hypotenuse dimension by 2 and divide by pi to obtain a design radius for a semicircular end panel 18. Multiply the span dimension by 1.0 to obtain the design length dimension for each suspension line 20 and slip-riser assembly 22 serial combination.

[047] After providing for typical seam and hem allowances, cut fourteen ~~inverted-goretrapezoidal gores 14~~, as illustrated by Fig 2, from an appropriate fabric and join them, as pairs, along their ~~spans-longer bases 38~~ to form seven canopy segments 16, as illustrated by Fig 3. Join the canopy segments 16, in series, along their ~~hypotenuse edges~~longitudinal sides 42, to

form a roughly rectangular canopy assembly 12 having a constructed chord dimension that is approximately 80% of the span dimension. Provide for typical seam and hem allowances and cut two semicircular end panels 18 from an appropriate fabric. Install an end panel 18 by its upper edge 36 in each outboard ~~end~~ longitudinal side 42 of the canopy assembly 12, as depicted by Fig 1. Mark and cut ~~fourteen~~ sixteen suspension lines 20, that when joined, serially, to the riser assemblies 22, will have a finished dimension that is approximately 100% of the canopy assembly 12 span dimension. Install one suspension line 20 at the ~~junction~~ intersection of the canopy assembly 12 skirt and each longitudinal seam ~~24~~ 48. Cut, and attach, six similar suspension lines 20, equally spaced, to the skirt of each end panel 18. Connect the free end of each suspension line 20 extending from the left front quarter of the canopy assembly 12 periphery to the left front slip-riser assembly 22 leg. Connect the free end of each suspension line 20 extending from the right front quarter of the canopy assembly 12 periphery to the right front slip-riser assembly 22 leg. Connect the free end of each suspension line 20 extending from the left rear quarter of the canopy assembly 12 periphery to the left rear slip-riser assembly 22 leg. Connect the free end of each suspension line 20 extending from the right rear quarter of the canopy assembly 12 periphery to the right rear slip-riser assembly 22 leg.

[048] It is quite feasible for the semi-cylindrical type parachute 10 to utilize conventional slip-riser assemblies 22 if controlled maneuvering is desired. When using the slip-riser maneuvering technique, the risers-slip-riser assemblies 22 for both sides of the parachute 10 can be manipulated, in unison, to cause a forward glide. By reversing the riser positions, a rearward glide will be produced. Because the semi-cylindrical type parachute 10 canopy plan form is much more wing-like than the canopy of the semispherical ballistic type parachute 24, the gliding performance is considerably more pronounced, and efficient, than that of a parachute

having a semispherical ballistic canopy. If the slip-riser assembly 22 on only one side of the parachute 10 is manipulated, the semi-cylindrical type parachute will make a heading change and the canopy can then be caused to glide in a new direction. Or, if desired, it can simply maintain the new heading, without glide. If an increased rate of descent is desired, the slip-riser assembly 22 on one side can be manipulated to cause a turn and, if the riser position remains unchanged, a spiraling turn will result.

[049] Spiraling turns are aerodynamically inefficient and the rate of descent will increase as a result. If, on the other hand, the riser assembly on one side is manipulated to cause a turn in one direction and the opposite riser assembly is manipulated in a similar fashion, the semi-cylindrical type parachute canopy will twist to become somewhat propeller-like, and spin about its vertical axis, producing lift, just as the spinning blades of a helicopter produce lift if the helicopter engine has lost power. Logically, when the parachute canopy begins producing lift it will have a decrease in its relative rate of descent.

[050] The very unique maneuvering capabilities of the semi-cylindrical type parachute 10, coupled with excellent economy of construction, is not known to exist with any other parachute type.

[051] As for parachutes of many other types, the designer of a semi-cylindrical type parachute 10 canopy can select from fabric offering the most desirable degree of permeability for a specific application, or the canopy can be made from strips of fabric, or ribbons, or be produced with specifically sized and located orifices, to produce a canopy with a specific geometric porosity and/or directional venting.

[052] It has been learned that the performance of the semi-cylindrical type parachute can be enhanced by having an end panel 18 installed in each end of the semi-cylindrical canopy assembly 12 to inhibit transverse airflow from the canopy interior. A semicircular end panel 18, completely filling the opening at each end of the quonset semi-cylindrical type parachute canopy, as depicted by Fig 1, is most effective but a partial panel, such as one shaped as a crescent, is somewhat effective and has less bulk than a semicircular end panel. However, a complete semicircular end panel will cause the inflated canopy shape to become somewhat elliptical, and will slightly increase the canopy span. If installed, end panels are considered to be components of the parachute canopy assembly.

[053] As is true for any type of wing-like gliding device, the gliding performance of the semi-cylindrical type parachute can be enhanced by increasing the span ratio, relative to the chord. The size and aspect ratio of the semi-cylindrical type parachute canopy is primarily dependent on the number of canopy segments utilized and/or the size of the canopy segments.

[054] Depending on loading conditions, it may be desirable to install suspension lines on the end panels of the semi-cylindrical type parachute canopy. Specific loading factors will dictate any end panel reinforcement required as well as the number of suspension lines required and the precise shape of the end panel will dictate the length of the suspension members.

[055] To properly manage the opening forces that to which a parachute is subjected to, it is frequently desirable to prolong the opening process of the parachute canopy by a technique known as reefing. It has been learned that the semi-cylindrical type parachute is compatible with all conventional reefing techniques such as peripheral reefing, spanwise reefing, or slider reefing.

Because of its simplicity and low cost, it is expected that slider reefing will typically be chosen when reefing is desired for the semi-cylindrical type parachute.

[056] Because of the very simple shape, the semi-cylindrical type parachute 10 can easily be constructed in modular form. For large scale semi-cylindrical type parachutes, modularity will allow convenient disassembly for handling or repair.

[057] As with all parachutes of all types, the parachute size, the suspended weight, and the predicted aerodynamic forces will dictate the number, and strength, of all materials for the design and construction of a semi-cylindrical type parachute, in addition to dictating the strength of seams and joints that must be used.

[058] Since other modifications and changes varied to fit particular operating requirements and environments will be apparent to those skilled in the art, the invention is not considered limited to the example chosen for purposes of disclosure, and covers all changes and modifications which do not constitute departures from the true spirit and scope of this invention.

[059] Having thus described the invention, what is desired to be protected by Letters Patent is presented in the subsequently appended claims.

ABSTRACT OF THE DISCLOSURE

A novel parachute design is presented that is distinguished by having ~~inverted-~~
~~ge~~trapezoidal gores, producing a parachute having a unique shape, which can be, selectively,
either ballistic or gliding and steerable, in addition to having a selectively variable rate of
descent. ~~Moreover, the parachute design allows for a very efficient use of materials.~~ The
parachute is comprised of a canopy assembly having plurality of laterally-aligned canopy
segments, each canopy segment shaped as an extended hexagon, formed by joining two isosceles
trapezoidal gores along their respective longer bases to form a centerline span, and each canopy
segment joined to adjacent canopy segments along a seam formed by the sides of adjacent gores.
The canopy is completed with semi-circular end panels, forming a semi-cylindrical canopy
assembly. Suspension lines are attached to the skirt of the canopy, which are joined at the lower
ends in a pair of suspension risers.